JK-6008T

Automatic pocket welting machine





Features

- 1. This machine is driven by servo motor, the biggest feature is that folding bag press frame and bag plate expansion are driven directly by motor. Fast speed, light voice and long service life are the characteristics of the machine. All the key parts are imported.
- 2. The bag opener is suitable for real bags, fake bags, T-shirt placket, especially the zipper of sports pants, which can be completed at one time, which is three times of the ordinary bag opener.
- 3. The folding mechanism of the automatic non-iron folding bag machine adopts the cylinder automatic folding technology, which improves the production efficiency and saves labor by eliminating the need for ironing table for folding pockets.
- 4. The automatic shrinkage mechanism of the internal pressure frame makes the change of the pocket's edge trace not limited. The internal pressure frame adds the function of replaceable adjustment.
- 5. Automatic feeding mechanism, after machine sewing, the automatic manipulator is used for feeding, and the sewing products can be placed neatly.



MORE INFORMATION

Technical Specfication

	UK 0000T
Model	JK-6008T
Sewing head speed	3000sti/min
Needle gauge	MT*190(12#、14#、16#)
Stitch programming	Input on operation screen
Pattern capacity	999 kinds
Stitch distance	1.0-3.5mm
Pressure foot rising height	60mm-80mm
Sewing pocket range	X direction 100mm-220mm Y direction 12mm-30mm
Speed of sewing pockets	10-15 seconds per second.
Folding method	Folding bags in 4 directions at the same time
Pocket opening way	Cutting with 100W laser head
Sewing methods	Pocket folding and sewing at the same time
Feeding Drive Mode	Servo motor drive (750w)
Power Supply	AC220V
Air Pressure	0.5Mpa(5kg/cm)、22dm³ /min
Packing size	1730x1380x1500mm

浙江劲悦机械科技有限公司 ZHEJIANG JOCKY MACHINERY TECHNOLOGY CO., LTD.