
JK390DD series




Double needle chain stitch Machine

JK390DD-1N JK390DD-2N(P) JK390DD-2N(T) JK390DD-3N JK390DD-3N(T) +PL 3-needles in a line Add puller device

1 needle 2 needles parallel 2 needles tandem 3 needles in triangle




1-needle chainstitch Parallel 2-needle chainstitch



3-needle chainstitch Tandem 2-needle chainstitch





Features

- 1/2/3 needles are available
- 2-needle model with stitch in parallel or tandem forms for option
- 3-needle model with needles in a row or triangle forms for option
- All models can add puller device for better feeding
- Pullers with flat rubber, gear rubber or gear metal for option
- Direct drive servo motor
- Auto needle positioning



JK390-1N



JK390-2N(P)



JK390-2N(T)



JK390-3N 3-needles in triangle




JK390-3N(T) 3-needles in a line



MORE INFORMATION

Technical Specfication

Model	JK390-2N
Needle number	2
Feed System	Bottom and Variable Top-Feed
Sewing speed	5,000 spm
Lubrication	Automatic
Needle type	TVX7 (#14)
Top Feed Amount	3mm
Looper stroke	30mm
Needle Bar	Fixed / Split Type
Looper System	Rocking type Looper
Motor	Servo Motor (220-240V AC, 550W)
G/N weight & volume	40/35kgs, 680*245*523mm=0.087cbm
Complete set	With stand & table with Synchronizer with caster Wheel







Gear rubber roller



Gear metal roller

浙江劲悦机械科技有限公司

ZHEJIANG JOCKY MACHINERY TECHNOLOGY CO., LTD.