

JK390DD series



Double needle chain stitch Machine

JK390DD-1N JK390DD-2N(P) JK390DD-2N(T) JK390DD-3N JK390DD-3N(T) +PL 1 needle 2 needles parallel 2 needles tandem 3 needles in triangle 3-needles in a line add puller device









Light	Medium	Heavy

Features

- 1/2/3 needles are available
- 2-needle model with stitch in parallel or tandem forms for option
- 3-needle model with needles in a row or triangle forms for option
- All models can add puller device for better feeding
- Pullers with flat rubber, gear rubber or gear metal for option
- Direct drive servo motor
- Auto needle positioning



JK390DD-1N



JK390DD-2N(P)



JK390DD-2N(T)



JK390DD-3N 3-needles in triangle



JK390DD-3N(T) 3-needles in a line



Flat rubber roller



Gear rubber roller



Gear metal roller



MORE INFORMATION

Technical Specification

Model	JK390-2N	
Needle number	2	
Feed System	Bottom and Variable Top-Feed	
Sewing speed	5,000 spm	
Lubrication	Automatic	
Needle type	TVX7 (#14)	
Top Feed Amount	3mm	
Looper stroke	30mm	
Needle Bar	Fixed / Split Type	
Looper System	Rocking type Looper	
Motor	Servo Motor (220-240V AC, 550W)	
G/N weight & volume	40/35kgs, 680*245*523mm=0.087cbm	
Complete set	With stand & table with Synchronizer with caster Wheel	