JK390DD series



Direct drive chainstitch sewing machine

JK390DD-1N JK390DD-2N(P) JK390DD-2N(T) JK390DD-3N JK390DD-3N(T) +PL 1 needle
2 needles parallel
2 needles tandem
3 needles in triangle
3-needles in a line
add puller device











Parallel 2-needle chainstitch









3-needle chainstitch Tandem 2-needle

Tandem 2-needle chainstitch

Features

- 1 /2 / 3 needles are available
- 2-needle model with stitch in parallel or tandem forms for option
- 3-needle model with needles in a row or triangle forms for option
- All models can add puller device for better feeding
- Pullers with flat rubber, gear rubber or gear metal for option
- Direct drive servo motor
- Auto needle positioning



JK390DD-1N



JK390DD-2N(P)



JK390DD-2N(T)



JK390DD-3N 3-needles in triangle



JK390DD-3N(T) 3-needles in a line



Flat rubber roller



Gear rubber roller



Gear metal roller



MORE INFORMATION

Technical Specification

Model	JK390DD-1N JK390DD-1N-PL	JK390DD-2N(P) JK390DD-2N(P)-PL JK390DD-2N(T) JK390DD-2N(T)-PL	JK390DD-3N JK390DD-3N-PL
Needle number	1	2	3
Max. speed	5,000sti/min		
Lubrication	Automatic		
Needle type	TVX7 (#14)		
Max. stitch length	4mm		
Needle bar stroke	30mm		
Pesser foot lift	5.5-10mm		
Bobbin thread winder	By hand: 5.5mm; By knee: 10mm		
Power	550W		
G/N weight & volume	40/35kgs, 680*245*523mm=0.087cbm		
Complete set	With stand & table 68kgs, 0.17cbm		