

# JPT-X15/20H

## LITHIUM PALLET TRUCK

**24** HOURS  
BUILT TO WORK




**JUKILIFT**

# SMART POWERFUL DURABLE

BUILT TO WORK  
**24**  
HOURS

## SMART SIZE

ALMOST SAME




## LIGHT WEIGHT




## EFFICIENCY

3 Times Higher Than Manual Pallet Truck



## EASY MAINTENANCE




## LIFETIME

3 Times Longer Than Manual Pallet Truck



1 PC VS 3 PCS



HIGH RETURN OF INVESTMENT

**Safety**

**PRODUCTIVE**

1 MONTH COST RECOVERY

Optimize your operations  
**SAVE LABOUR**  
Release manpower  
Brake any time anywhere

# Powerful With High Gradeability



## Unique brushless technology

Brushless motor, powerful and maintenance free.  
Leading in the industry.



**750W/1000W power**  
**Brushless motor**  
**Maintenance free**



**Powered traveling**




**Powered lifting & lowering**

## Maintenance free

For brushed motor, carbon brush needs to be replaced every 12 or 18 months.  
For JPT-X15H, no need to replace carbon brush.  
Maintenance-free, saving maintenance time and cost.



## Powerful with high gradeability

To easily move 1.5 ton or 2 ton over the slopes at warehouse entrances.



**Traveling speed**

— **UNLADEN** 4.5km/h  
+ **LADEN** 4km/h



**Gradeability**



# Non-stop Working

## 6s to replace battery



Maintenance-free lithium battery  
It takes only 6s to replace battery.  
With a spare battery, the unit can keep working 24 hours.

## Short charging time Charge and use freely

Quick charging: 2 hours to fully charge the battery.

## Ensured battery safety

Safe and reliable, no fire, no explosion.  
Complying with IEC, UL global standard certification requirements,  
ensuring the safety of user property.

- Long service life: lithium battery with a long service life.
- High safety performance: it adopts soft package battery technology, built-in protection board and multiple protection to eliminate overcharge and overdischarge.
- Maintenance free: no need to add water.



## Compact and durable

### Solid build, no breaking


Chassis made by solid materials, no bending, no deformation.  
Reinforced rocker arm, push rod, wheel frame and support seat.  
No plastic part, less damage.

### Most compact unit with same lifting capacity

Suitable for small workplaces such as compact workshops,  
trucks or vans, tail lifts or elevators.  
JPT-X15H has the smallest turning radius among similar products.

### Integral forks, no splicing


The forks are uniquely designed, easy to handle European  
pallets, American pallets and plastic pallets.  
Solid fork with no deformation, far more durable than other  
brands of the same category.




# Intelligent Control

When you're moving heavy loads in tight spaces, maneuverability and controllability are critical to ensure safety, productivity and comfort.

The core concept of JUKILIFT products is to make your job easier. With the ergonomically designed handle, JPT-X15H is easy to operate, reduces fatigue and improves work efficiency. Compared to other brands, users prefer to use JUKILIFT JPT series.



## Operator Preferred



- ⚠ In up-right drive mode, vehicle will move when handle is operated at any position. Please avoid misoperation.
- ⚠ Brake release mode is only for emergencies, not allowed for vehicle with normal conditions.

### Comfortable Operation

Easy to operate  
Ergonomic handle, comfortable to use.

### Leading Technology

CanBus technology is applied on this entry-level electric pallet truck.

### Fast And Slow Speed

To match different levels of operator experience, and varied work environments.

### Up-right Drive Mode

Convenient to operate in vans, on tail lifts, or inside elevators.

### Engineering Mode

When the unit breaks down, it can be moved away manually.

- 🔌 Recharge alert
- 🕒 Hour meter
- 🎯 Powered traveling
- ⬆️⬆️ Powered lifting & lowering
- ⚠ Error code display
- 🛑 Emergency stop button
- 🔊 Horn

### Slope anti-sliding design

Easy parking on slopes, preventing accidental backing of the machine.

# Easy Maintenance

JPT series utilizes JUKILIFT's integrated diagnostics, error code display and JUKILIFT's original service mini-program to facilitate quick problem resolution.

## Easy parts replacement


The unique design makes disassembly and assembly simple, reducing machine downtime and operating costs.

- **1 minute**  
**Replace the drive wheel**
- **1 minute**  
**Replace the handle**
- **2 minutes**  
**Remove the controller**
- **3 minutes**  
**Remove the motor**



### Error Code Display

Quickly identify the fault during operation.




### Professional after-sales support

Specialist guidance is a phone call away.

## Ready to Handle Multiple Jobs

With its unique design, JPT series is powerful and maneuverable to meet the application in a wide range of working conditions.



Warehouses/Logistics center



Truck tail lift



Supermarket

Pallet trucks are a necessary investment. Choosing the wrong machine could cause loss in productivity, high cost of machine downtime, unhappy workers, and overall, increased running costs. Choosing JPT series will reward you with long-term value.


## JUKILIFT Series

- **Powerful**
- **Durable**
- **Easy maintenance**
- **Low use cost**
- **High return on investment**


# Basic Configuration

**Horn**  
**Emergency reverse button**  
**Forward/reverse butterfly switch**  
**Lifting / Lowering**  
**LCD Screen**

- ◆ Battery indicator with hour meter
- ◆ Error code display
- ◆ Recharge alert



**Multi-function Handle (Full Electric)**



**Multi-function Ergonomic Handle (Semi-electric)**



**Tandem/Single PU wheel**



**JPT-X15HL**

**JPT-X15/20H**



**Low profile forks**  
 Lowered fork height: 65mm  
 Standard model: 82mm



**Lithium Battery**




**Protection cover**  
 Protect the drive motor,  
 Anti-foot stamping



**Intelligent charger**



**Electric lifting/lowering**



**Manual lifting/lowering**

# Optional Configuration

- Key button
- Upright driving button
- Max speed setting button
- Horn button




**Intelligent Control Key**



**48V 15Ah battery with bigger capacity**  
Longer working hour



**5A fast charger**  
Shorter charging hour



### Load backrest

When goods are stacked high, the load backrest can prevent it from falling, ensuring user safety.



### Balance wheel

More stable

FORK LENGTH (mm) 800/900/1150/1220/1500



### Fork length


800/900/1150/1220/1500mm fork length options



**Wrapping film holder**



# Dimensions



# Specifications

MODEL		JPT-X20HS	JPT-X15H	JPT-X20H	JPT-X15HL
<b>CHARACTERISTICS</b>					
1.1	Drive		Electric	Electric	Electric
1.2	Operator type		Pedestrian	Pedestrian	Pedestrian
1.3	Load capacity/rated load	Q kg	2000	1500	2000
1.4	Load centre	C mm	600	600	600
1.5	Height, fork lowered	h <sub>13</sub> mm	82 ± 2	82 ± 2	82 ± 2
1.6	Wheelbase	y mm	1197/1267	1197/1267	1197/1267
1.7	Wheel		PU	PU	PU
1.8	Wheel size, front	mm	140*55	140*55	140*55
1.9	Wheel size, rear	mm	80*93 (Single Wheel)	80*93 (Single Wheel)	80*93 (Single Wheel)
		mm	80*70 (Tandem)	80*70 (Tandem)	80*70 (Tandem)
1.10	Wheels, number front/rear (x = drive wheels)		1x+2/4	1x+2/4	1x+2/4
1.11	Lift	h <sub>3</sub> mm	115	115	115
1.12	Height of tiller in drive position, min./max.	h <sub>14</sub> mm	740/1220	740/1220	740/1220
1.13	Overall length	L <sub>1</sub> mm	1552/1622	1552/1622	1552/1622
1.14	Fork Length	L mm	1150/1220	1150/1220	1150/1220
1.15	Overall width	b <sub>1</sub> mm	550/685	550/685	550/685
1.16	Fork dimensions	mm	58/160/1150(1220)	58/160/1150(1220)	58/160/1150(1220)
1.17	Distance between fork-arms	b <sub>5</sub> mm	550/685	550/685	550/685
1.18	Ground clearance, centre of wheelbase	m <sub>2</sub> mm	22/137(24/139)	22/137(24/139)	22/137(24/139)
1.19	Aisle width for pallets 1000x1200 crossways	A <sub>st</sub> mm	2155/2226	2155/2226	2155/2226
1.20	Aisle width for pallets 800x1200 lengthways	A <sub>st</sub> mm	2024/2064	2024/2064	2024/2064
1.21	Turning radius	W <sub>a</sub> mm	1353/1426	1353/1426	1353/1426
<b>PERFORMANCE</b>					
2.1	Travel speed, laden/unladen	km/h	4.0/4.5	4.0/4.5	4.0/4.5
2.2	Lifting speed, laden/unladen	mm/s	/	18/23	18/23
2.3	Lowering speed, laden/unladen	mm/s	/	56/46	56/46
2.4	Max. gradeability, laden/unladen	%	6%/20%	6%/20%	6%/20%
2.5	Drive motor	kW	DC 1.0 Brushless	DC 0.75 Brushless	DC 1.0 Brushless
2.6	Lift motor	kW	Hydraulic	DC 0.8	DC 0.8
<b>BATTERY</b>					
3.1	Battery voltage/nominal capacity	V/Ah	48V/10Ah(48V/15Ah)	48V/10Ah(48V/15Ah)	48V/10Ah(48V/15Ah)
3.2	Traveling brake		Regenerate	Regenerate	Regenerate
3.3	Brake		Electromagnetic	Electromagnetic	Electromagnetic
3.4	Sound level at the driver's ear according to EN 12053	A	< 70dB	< 70dB	< 70dB
3.5	Service weight including battery	kg	117/123.5	116.5/123	119/125.5